NEW 1,54" COG OLED Display

Winstar introduced the new 1,54" COG graphic OLED display module. This is built-in with SH1106 IC; it can communicate via I2C, 4-wire SPI, 6800 or 8080 interface. The supply voltage of logic is $1.65~V \sim 3.3~V$, the supply voltage for display is $6.4V \sim 13V$, 1/64~V driving duty. Best Suitable for: Medical devices, consumer electronics, industrial automation, and smart home devices.



Item	Contents	Unit
Module Dimensions	42.04 × 27.22 × 1.41	mm
Size	1,54	inch
Dot Matrix	128 × 64	dots
Active Area	35.05 × 17.51	mm
Pixel Size	0.249×0.249	mm
Pixel Pitch	0.274 × 0.274	mm
Display Mode	Passive Matrix	
Display Color	Monochrome	
Drive Duty	1/64 Duty	
IC	SH1106	
Interface	6800,8080,4-wire SPI,I2C	



Model Features:

> Type: Graphic > Structure: COG > Size: 1.54"

> 128 x 64 Dot Matrix

>IC: SH1106

>3V Power Supply

>1/64 Duty

>Interface: 6800,8080,SPI,I2C >Display Color: White/Yellow

> Operating Temperature Range: -40° C to $+80^{\circ}$ C > Storage Temperature Range: -40° C to $+85^{\circ}$ C

